

Description

Diameter: 23/64", steel comp

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CA180910HS
Minimum Qty (MOQ):	1
NSN:	5325-01-030-7016
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N CA18091-0HS Specifications

Grip Length:	0.093 Inches Minimum And 0.150 Inches Maximum
Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Securing Device Type:	Washer
Turnlock Stud Shank Style:	Stud Shank
Extension Length:	0.210 Inches Nominal
Turnlock Stud Head Style:	Fillister
Drive Type:	Socket
Stud Thread Size And Series/type Designator:	0.164-32 Unc
Stud Shank Major Diameter:	0.2470 Inches Minimum And 0.2495 Inches Maximum
Material:	Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	66 Fed Std 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall Or Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this captive fastener from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+receptacles/CA18091-0HS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.