

Description

Diameter: 21/64", steel corrosion resisting overall

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | CA182361         |
| Minimum Qty (MOQ): | 2                |
| NSN:               | 5325-01-606-1541 |



\* See page 2 for technical characteristics

## P/N CA18236-1 Specifications

|   |   |
|---|---|
| <b>Grip Length:</b>                                   | 0.637 Inches Nominal  |
| <b>Diameter:</b>                                      | 0.330 Inches Nominal  |
| <b>Turnlock Stud Head Style:</b>                      | Flat Countersunk  |
| <b>Drive Type:</b>                                    | Socket  |
| <b>Stud Thread Size And Series/type Designator:</b>   | 0.164-32-3b Unc   |
| <b>Stud Shank Major Diameter:</b>                     | 0.2470 Inches Minimum And 0.2495 Inches Maximum   |
| <b>Material:</b>                                      | Steel Corrosion Resisting Overall   |
| <b>Material Document And Classification:</b>          | Astm A581 Assn Std Single Material Response Or Astm A582 Assn Std Single Material Response Or Astm A320 Assn Std Single Material Response Or Ams 5640 Assn Std Single Material Response Or Ams 5640 Assn Std Single Material Response Or Ams 5738 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall  |

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/CA18236-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.