

P/N CA18236-3

Description

Diameter: 21/64", steel comp 303or steel comp 303seor steel comp 316 overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CA182363
Minimum Qty (MOQ):	1
NSN:	5325-01-090-7232
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



^{*} See page 2 for technical characteristics

P/N CA18236-3 Specifications

Grip Length:	0.344 Inches Minimum And 0.437 Inches Maximum
Diameter:	0.330 Inches Minimum
Securing Device Type:	Grommet
Turnlock Stud Shank Style:	Stud Shank
Extension Length:	0.190 Inches Nominal
Turnlock Stud Head Style:	Flat Countersunk
Material Accommodated Thickness:	0.344 Inches Minimum And 0.437 Inches Maximum
Drive Type:	Socket
Stud Thread Size And Series/type Designator:	0.164-32 Unc
Stud Shank Major Diameter:	0.2470 Inches Minimum And 0.2495 Inches Maximum
Material:	Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 316 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud from our inventory online by visiting https://military-fasteners.com/studs/turnlock+fastener+studs/CA18236-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/studs/turnlock+fastener+studs/CA18236-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/studs/turnlock+fastener+studs/CA18236-3 and selecting the