

**Description**

Diameter: 19/64", steel comp

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CA20231S
Minimum Qty (MOQ):	1
NSN:	5325-00-225-1428
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CA2023-1S Specifications

<b>Grip Length:</b>	0.125 Inches Minimum And 0.187 Inches Maximum
<b>Diameter:</b>	0.300 Inches Minimum
<b>Securing Device Type:</b>	Ring
<b>Turnlock Stud Shank Style:</b>	Stud Shank
<b>Extension Length:</b>	0.130 Inches Nominal
<b>Turnlock Stud Head Style:</b>	Flat Countersunk
<b>Drive Type:</b>	Slotted Or Socket
<b>Stud Thread Size And Series/type Designator:</b>	0.112-40 Unc
<b>Stud Shank Major Diameter:</b>	0.184 Inches Minimum And 0.186 Inches Maximum
<b>Material:</b>	Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Astm A582 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/CA2023-1S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.