

Description

Diameter: 19/64", steel comp 303 overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | CA20232S |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5325-00-794-2675 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CA2023-2S Specifications

| | |
|---|---|
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Diameter: | 0.300 Inches Minimum |
| Securing Device Type: | Ring |
| End Item Identification: | W/s: Aircraft, Prowler Ea-6b; Test Consoles, Mini-sace; Aircraft, Airlifter C-17a; Aircraft, Hawkeye E-2c; Aircraft, C-2a (reprocured); Aircraft, F-111 |
| Turnlock Stud Shank Style: | Stud Shank |
| Extension Length: | 0.130 Inches Nominal |
| Turnlock Stud Head Style: | Flat Countersunk |
| Drive Type: | Slotted Or Socket |
| Stud Thread Size And Series/type Designator: | 0.112-40 Unc |
| Stud Shank Major Diameter: | 0.184 Inches Minimum And 0.186 Inches Maximum |
| Material: | Steel Comp 303 Overall |
| Material Document And Classification: | Astm A582 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |

How to Order

Order this stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/CA2023-2S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.