

Description

Diameter: 19/64", steel comp 303 overall

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CA20232S
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-794-2675
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CA2023-2S Specifications

Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Diameter:	0.300 Inches Minimum
Securing Device Type:	Ring
End Item Identification:	W/s: Aircraft, Prowler Ea-6b; Test Consoles, Mini-sace; Aircraft, Airlifter C-17a; Aircraft, Hawkeye E-2c; Aircraft, C-2a (reprocured); Aircraft, F-111
Turnlock Stud Shank Style:	Stud Shank
Extension Length:	0.130 Inches Nominal
Turnlock Stud Head Style:	Flat Countersunk
Drive Type:	Slotted Or Socket
Stud Thread Size And Series/type Designator:	0.112-40 Unc
Stud Shank Major Diameter:	0.184 Inches Minimum And 0.186 Inches Maximum
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A582 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this stud from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+studs/CA2023-2S> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.