

## P/N CA21037-4-2HS

### **Description**

Fastener Length: 63/64", Thread: 1/4-28, Head Width: 9/64", Thread Length: 17/32",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: CA2103742HS

Minimum Qty (MOQ):

NSN: 5306-01-055-9093

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N CA21037-4-2HS Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.520 Inches Nominal
Fastener Length:	0.972 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.140 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

## **How to Order**

Order this internal wrenching bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/internal+wrenching+bolts/CA21037-4-2HS">https://military-fasteners.com/bolts/internal+wrenching+bolts/CA21037-4-2HS</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/internal+wrenching+bolts/CA21037-4-2HS">https://military-fasteners.com/bolts/internal+wrenching+bolts/CA21037-4-2HS</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/internal+wrenching+bolts/CA21037-4-2HS">https://military-fasteners.com/bolts/internal+wrenching+bolts/CA21037-4-2HS</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/ca21037-4-2HS">https://military-fasteners.com/bolts/ca21037-4-2HS</a> and selecting the property of the property