

Description

Fastener Length: 1-25/64", Thread: 1/4-28, Head Width: 9/64", Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CA2103748HS
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-051-3467
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N CA21037-4-8HS Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.682 Inches Minimum And 0.821 Inches Maximum
Fastener Length:	1.392 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.141 Inches Minimum And 0.143 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Special Features:	1.247 In. Lg Groove And Wire Formspring Hold Out Device
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Acme

How to Order

Order this stud from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/CA21037-4-8HS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.