

P/N CA21037-6-4HS

Description

Fastener Length: 1-13/64", Thread: 3/8-24, Head Width: 9/64", Thread Length: 13/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	CA2103764HS
Minimum Qty (MOQ):	1
NSN:	5306-01-053-9319
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N CA21037-6-4HS Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.840 Inches Nominal
Fastener Length:	1.210 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.375 Inches Nominal
Locking Feature:	Slotted Concentric Hole
Internal Drive Style:	Hexagon
End Item Identification:	An/ale-40
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.141 Inches Nominal
Features Provided:	Retaining Clip
Thread Quantity Per Inch:	24
Countersink Angle:	100.0 Degrees Nominal
Externally Relieved Body Diameter Quantity:	1
Special Features:	Externally Relieved Portion 0.100in. Lg At Tip Of Thread End; concentrichole Through Threaded Portion To Accomodate Retaining Clip-locking Feature
Material:	Steel Comp 4140 Overall And Steel Comp 8740 Overall
Material:	Steel Comp 631 Locking Feature
Material Document And Classification:	Ams 5673 Assn Std Single Material Response Locking Feature
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment:	Passivate Locking Feature
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Feature
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

