

Description

Thread: 1/4-28, Head Width: 1/8", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CA21046HS
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-054-6634
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N CA2104-6HS Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.487 Inches Nominal
Fastener Length:	1.047 Inches Minimum And 1.067 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.360 Inches Minimum And 0.399 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.156 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Special Features:	Double Lead Thd
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/CA2104-6HS> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.