

P/N CA21062-06-4-9

Description

Fastener Length: 1/2", Thread: 6-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: CA210620649

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-307-8651

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N CA21062-06-4-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.337 Inches Nominal
Fastener Length:	0.562 Inches Nominal
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Point Length:	0.090 Inches Minimum And 0.095 Inches Maximum
Point Diameter:	0.100 Inches Maximum
Point Style:	Flat
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Point Chamfer Angle:	45.0 Degrees Nominal
Special Features:	Two Slots On Screw 0.034 In. Min,0.044 In. Max W; 0.482 In. Max Lg
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 304l Overall Or Steel Comp 305 Overall Or Steel Comp 309 Overall Or Steel Comp 310 Overall Or Steel Comp 316 Overall Or Steel Comp 317 Overall Or Steel Comp 321 Overall Or Steel Comp 322 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Qq-s-763 Fed Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/CA21062-06-4-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.