

## P/N CA21062-10-3-11

### **Description**

Fastener Length: 11/16", Thread: 10-32

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: CA2106210311

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-270-0074

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



# P/N CA21062-10-3-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.677 Inches Minimum And 0.697 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.121 Inches Minimum And 0.133 Inches Maximum
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.084 Inches Minimum And 0.104 Inches Maximum
Thread Quantity Per Inch:	32
Special Features:	Two Keyways Along Threads 180 Deg Apart; Width Of Keyways 0.044 In. Min. And 0.054 In. Max
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 304l Overall Or Steel Comp 305 Overall Or Steel Comp 309 Overall Or Steel Comp 310 Overall Or Steel Comp 316 Overall Or Steel Comp 316l Overall Or Steel Comp 317 Overall Or Steel Comp 321 Overall Or Steel Comp 322 Overall Or Steel Comp 324 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Qq-s-763 Fed Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/CA21062-10-3-11">https://military-fasteners.com/screws/machine+screws/CA21062-10-3-11</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.