

Description

Fastener Length: 27/32", Thread: 10-, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CA22043100300
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-465-7825
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N CA22043-10-0300 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.430 Inches Minimum And 0.470 Inches Maximum
Fastener Length:	0.850 Inches Nominal
Head Style:	Undercut Pan No. 2
Head Diameter:	0.482 Inches Nominal
Head Height:	0.200 Inches Minimum And 0.240 Inches Maximum
Internal Drive Style:	Hexagon
End Item Identification:	Ah-64
Material Accommodated Thickness:	0.108 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Lead Thread Quantity:	Two
Material:	Iron Alloy 660 Fastener
Material:	Steel Comp 302 Spring
Material:	Steel Corrosion Resisting Stand-off
Material Document And Classification:	Ass 5640 Assn Std Single Material Response Stand-off Or Astm A555 Assn Std Single Material Response Stand-off Or Astm A581 Assn Std Single Material Response Stand-off
Material Document And Classification:	Ast-5731 Assn Std Single Material Response Fastener Or Astm 5732 Assn Std Single Material Response Fastener
Material Document And Classification:	Astm A313 Assn Std Single Material Response Spring
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/CA22043-10-0300> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.