

P/N CA22043-10-0360

Military-Fasteners.com

#### Description

Fastener Length: 39/64", Thread: 10-32, Thread Length: 15/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	CA22043100360
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-465-7827
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N CA22043-10-0360 Specifications

Thread Diract   Bar     Thread Diract   Right-hand     Thread Length:   0.430 Inches Minimum And 0.470 Inches Maximum     Fastenr Length:   0.610 Inches Moninal     Head Style:   Undercut Pan No. 2     Head Diameter:   0.482 Inches Moninal     Head Height:   0.200 Inches Minimum And 0.240 Inches Maximum     Head Height:   0.482 Inches Moninal     Head Height:   0.200 Inches Minimum And 0.240 Inches Maximum     Internal Drive Style:   Hexagon     Material Accommodated Thicknes:   0.108 Inches Noninal     Noninal Thread Diameter:   0.190 Inches     Material Accommodated Thicknes:   0.190 Inches     Noninal Thread Quantity Per Inch:   32     Screw,captive,self-retracting,crimp-ring Style   Screw,captive,self-retracting,crimp-ring Style     Lead Thread Quantity:   Kore (Sorgion Resisting Stand-off     Material:   Screw (Caption Resisting Stand-off     Material:   Scel Corrosion Resisting Stand-off     Material Document And Classification:   Ams Stol Single Material Response Stand-off Chasten Stand-off Chasten Stand-off Chasten Stand-off Chasten Stand-off Chasten Stand-off Chasten Stand Stangle Material Response Stand-off Chasten Stand-off Chasten S	Thread Class:	За
Thread Length:0.430 Inches Minimum And 0.470 Inches MaximumFastener Length:0.610 Inches NominalHead Style:Undercut Pan No. 2Head Diameter:0.482 Inches NominalHead Height:0.200 Inches Minimum And 0.240 Inches MaximumInternal Drive Style:HexagonInternal Drive Style:No.64Material Accommodated Thicknes:0.108 Inches NominalNominal Thread Diameter:0.109 InchesOndersträck Style:0.109 InchesMaterial Accommodated Thicknes:0.109 InchesNominal Thread Diameter:0.109 InchesOndersträck Style:0.109 InchesMaterial Accommodated Thicknes:0.100 Pounds Per Square InchMaterial Stength:16000 Pounds Per Square InchPared Quantity Per Inch:Scew.captive.self-retracting.crimp-ring StyleParent Quantity:roSpecial Features:Grip Length 0.350 InchMaterial Response Stand-offStel Comp 302 SpringMaterial Document AndStel Comp 302 SpringMaterial Document AndStel Stang Stand Stang Stand-offMaterial Document Andma Staf Assn Std Single Material Response Stand-off Cox Stang S		
Fastener Length:0.610 Inche NominalHead Style:Undercut Pan No. 2Head Dameter:0.420 Inche NominalHead Height:0.200 Inche Minimu And 0.240 Inches MaximumInternal Drive Style:HeagonInternal Drive Style:No.64Material Accommodated Thickes:0.100 Inches NominalMaterial Accommodated Thickes:0.100 Inches NominalNominal Thread Diameter:0.100 Inches Casuanci Accommodated Thickes:Nominal Thread Diameter:0.100 Inches Style:Material Storength:1000 Pounds Per Square InchMaterial Accommodated Thickes:1000 Pounds Per Square InchMaterial Storength:1000 Pounds Per Square InchMaterial Storength:1000 Pounds Per Square InchSpecial Features:Gri Length 0.50 InchMaterial:No.100 Square InchMaterial:No.100 Square InchMaterial:Sci Coroson Resident Square InchMaterial:Sci Coroson Resident Square InchMaterial:Sci Coroson Resident Square InchMaterial:Sci Coroson Resident Square InchMaterial Document AndSci Sci Coroson Resident Square Squar		-
Head Style:Indercut Pan No. 2Head Diameter:0.482 Inches NominalHead Height:0.200 Inches Minimum And 0.240 Inches MaximumInteral Drive Style:Heag OneInteral Drive Style:No. 40Material Accommodated Thicknes:0.108 Inches NominalOntinal Thread Diameter:0.108 Inches NominalNominal Thread Diameter:0.109 InchesMaterial Accommodated Thicknes:0.109 InchesMaterial Strength:1000 Pounds Per Square InchMaterial Strength:rew., captive, self-retracting, crimp-ring StyleMaterial:rew., captive, self-retracting, crimp-ring StyleActerial:rew. Captive, self-retracting, crimp-ring StyleMaterial:Non Allog 606 FastenerMaterial:rew. Cartonia StolenchMaterial:Scel Comp 302 SpringMaterial:Scel Comp 302 SpringMaterial Document And Classification:scil Stalf Active Stolench Stalf Stalf Meterial Response Stand-offMaterial Document And Classification:ans Stal Stalf Single Material Response Stand-off Stalf Sta	Thread Length:	0.430 Inches Minimum And 0.470 Inches Maximum
Head Diameter:0.482 Inches NominalHead Height:0.200 Inches Minimum And 0.240 Inches MaximumInternal Drive Style:HexagonEnd Item Identification:Ah-64Material Accommodated Thickness:0.108 Inches NominalNominal Thread Diameter:0.190 Inches0.190 Inches1.900 Pounds Per Square InchThread Quantity Per Inch:32Material Strength:160000 Pounds Per Square InchPar Name Assigned By Controlling Agency:crew,captive,self-retracting,crimp-ring StyleSpecial Features:Grip Length 0.350 InchMaterial:Ton Alloy 660 FastenerMaterial:Steel Corms 302 SpringMaterial:Steel Corms 302 SpringMaterial:Steel Corms 302 SpringMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Stand-off Or Astm A555 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response SpringMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Spring	Fastener Length:	0.610 Inches Nominal
Head Height:0.200 Inches Minimum And 0.240 Inches MaximumInternal Drive Style:HexagonEnd Item Identification:Ah-64Material Accommodated Thickness:0.108 Inches NominalNominal Thread Diameter:0.109 InchesOther Style:1.000 Pounds Per Square InchBrand Quantity Per Inch:32Brand Assigned By Controlling:crew, captive, self-retracting, crimp-ring StylePart Name Assigned By Controlling:TwoSpecial Features:Grip Length 0.350 InchMaterial:Two Inclus Go PastenerMaterial:Steel Corrosion Resisting Stand-offMaterial Document And Classification:Steel Corrosion Resisting Stand-offMaterial Document And Classification:Ams 540 Assn Std Single Material Response Fastener Or Ams 5573 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response	Head Style:	Undercut Pan No. 2
Internal Drive Style:HexagonEnd Item Identification:Ah-64Material Accommodated Thickness:0.108 Inches NominalNominal Thread Diameter:0.109 InchesThread Quantity Per Inch:32Minium Tensile Strength:16000 Pounds Per Square InchPar Name Assigned By Controlling Agency:Trew.captive,self-retracting,crimp-ring StyleLead Thread Quantity:TwoSpecial Features:Grip Length 0.350 InchMaterial:Ional Job ControllingMaterial:Stel Corrosion Resisting Stand-offMaterial:Stel Corrosion Resisting Stand-offMaterial Document And Classification:Stel Stange Material Response Stand-offMaterial Document And Classification:Stan Stal Single Material Response Stand-off	Head Diameter:	0.482 Inches Nominal
End Item Identification:Ah-64Material Accommodated Thickness:0.108 Inches NominalNominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchPar Name Assigned By Controlling Agency:crew.captive.self-retracting.crimp-ring StyleLead Thread Quantity:TwoSpecial Features:Grip Length 0.350 InchMaterial:Ion Alloy 660 FastenerMaterial:Steel Comp 302 SpringMaterial:Steel Comp 302 SpringMaterial:Steel Corrosion Resisting Stand-offMaterial Document And Classification:sh 531 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response SpringMaterial Document And Classification:ch 313 Assn Std Single Material Response Spring	Head Height:	0.200 Inches Minimum And 0.240 Inches Maximum
Material Accommodated Thickness0.108 Inches NominalNominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchPart Name Assigned By Controlling Agency:crew,captive,self-retracting,crimp-ring StyleLead Thread Quantity:TwoSpecial Features:Grip Length 0.350 InchMaterial:Ionn Alloy 660 FastenerMaterial:Stel Corros Organity StandorffMaterial:Stel Corros Organity StandorffMaterial:Stel Corros Organity StandorffMaterial Document And Classification:Sry 513 Assn Std Single Material Response Stand-offMaterial Document And Classification:Sry 513 Assn Std Single Material Response Stand-offMaterial Document And Classification:Sry 513 Assn Std Single Material Response Stand-offMaterial Document And Classification:Sry 513 Assn Std Single Material Response Stand-offMaterial Document And Classification:Sry 513 Assn Std Single Material Response Stand-offMaterial Document And Classification:Sry 513 Assn Std Single Material Response Stand-offMaterial Document And Classification:Sry 513 Assn Std Single Material Response Stand-offMaterial Document And Classification:Sry 513 Assn Std Single Material Response Stand-offMaterial Document And Classification:Sry 513 Assn Std Single Material Response Stand-offMaterial Document And Classification:Stel Single Material Response StandorffMaterial Document And Classification:Stel Single Material Response Sprin	Internal Drive Style:	Hexagon
Nominal Thread Diameter:0.190 InchesNominal Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchPart Name Assigned By Controlling Agency:Crew,captive,self-retracting,crimp-ring StyleLead Thread Quantity:TwoSpecial Features:Grip Length 0.350 InchMaterial:Iron Alloy 660 FastenerMaterial:Steel Comp 302 SpringMaterial:Steel Comp 302 SpringMaterial Document And Classification:Ams 5640 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response SpringMaterial Document And Classification:Ams 5731 Assn Std Single Material Response SpringMaterial Document And Classification:Ams 5731 Assn Std Single Material Response SpringMaterial Document And Classification:Ams 5731 Assn Std Single Material Response SpringMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Spring	End Item Identification:	Ah-64
Thread Quantity Per Inch:32Minimum Tensile Strength:60000 Pounds Per Square InchPart Name Assigned By Courlingcrew,captive,self-retracting,crimp-ring StyleLead Thread Quantity:TwoLead Thread Quantity:Grip Length 0.350 InchMaterial:Inchlog Go FastenerMaterial:Inchlog Go FastenerMaterial:Stel Cornosion Resisting Stand-offMaterial Document And Classification:ms 5640 Assn Std Single Material Response Fastener Or Assn Std Single Material Response Stand-offMaterial Document And Classification:ms 5731 Assn Std Single Material Response Stand-offMaterial Document And Classification:ms 5731 Assn Std Single Material Response Stand-offMaterial Document And Classification:ms Stand Single Material Response Stand-off	Material Accommodated Thickness:	0.108 Inches Nominal
Minimum Tensile Strength:160000 Pounds Per Square InchPart Name Assigned By Controlling Agency:Screw.captive.self-retracting.crimp-ring StyleLead Thread Quantity:TwoEad Thread Quantity:Grip Length 0.350 InchMaterial:Iron Alloy 660 FastenerMaterial:Steel Comp 302 SpringMaterial:Steel Corrosion Resisting Stand-offMaterial Document And Classification:Mas 540 Assn Std Single Material Response Stand-off Or Astm A555 Assn Std Single Material Response Stand-offMaterial Document And Classification:Mas 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response FastenerMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Spring	Nominal Thread Diameter:	0.190 Inches
Part Name Assigned By Controlling Agency:Screw,captive,self-retracting,crimp-ring StyleLead Thread Quantity:TwoSpecial Features:Grip Length 0.350 lnchMaterial:Iron Allog 60 FastenerMaterial:Steel Comp 302 SpringMaterial Document And Classification:Stes 640 Assn Std Single Material Response Stand-offMaterial Document And Classification:Mats 551 Assn Std Single Material Response Stand-offMaterial Document And Classification:Mats 731 Assn Std Single Material Response SpringMaterial Document And Classification:Ams S731 Assn Std Single Material Response SpringMaterial Document And Classification:Ams S731 Assn Std Single Material Response SpringMaterial Document And Classification:Ams S731 Assn Std Single Material Response SpringMaterial Document And Classification:Ams S731 Assn Std Single Material Response Spring	Thread Quantity Per Inch:	32
Agency:Screw, captive, self-retracting, crimp-ring StyleLead Thread Quantity:TwoSpecial Features:Grip Length 0.350 InchMaterial:Iron Alloy 660 FastenerMaterial:Steel Comp 302 SpringMaterial:Steel Corrosion Resisting Stand-offMaterial Document And Classification:Ams 5640 Assn Std Single Material Response Stand-off Or Astm A555 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response FastenerMaterial Document And Classification:Astm A313 Assn Std Single Material Response Spring	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Special Features:Grip Length 0.350 InchMaterial:Iron Alloy 660 FastenerMaterial:Steel Comp 302 SpringMaterial:Steel Corrosion Resisting Stand-offMaterial Document And Classification:Ams 5640 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response FastenerMaterial Document And Classification:Ams 3731 Assn Std Single Material Response Spring		Screw,captive,self-retracting,crimp-ring Style
Material:Iron Alloy 660 FastenerMaterial:Steel Comp 302 SpringMaterial:Steel Corrosion Resisting Stand-offMaterial Document And Classification:Ams 5640 Assn Std Single Material Response Stand-off Or Astm A555 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response FastenerMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Spring	Lead Thread Quantity:	Тwo
Material:Steel Comp 302 SpringMaterial:Steel Corrosion Resisting Stand-offMaterial Document And Classification:Ams 5640 Assn Std Single Material Response Stand-off Or Astm A555 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response FastenerMaterial Document And Classification:Astm A313 Assn Std Single Material Response Spring	Special Features:	Grip Length 0.350 Inch
Material:Steel Corrosion Resisting Stand-offMaterial Document And Classification:Ams 5640 Assn Std Single Material Response Stand-off Or Astm A555 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response FastenerMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response Fastener	Material:	Iron Alloy 660 Fastener
Material Document And Classification:Ams 5640 Assn Std Single Material Response Stand-off Or Astm A555 Assn Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response FastenerMaterial Document And Classification:Ams 3731 Assn Std Single Material Response Spring	Material:	Steel Comp 302 Spring
Classification:Std Single Material Response Stand-offMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response FastenerMaterial Document And Classification:Astm A313 Assn Std Single Material Response Spring	Material:	Steel Corrosion Resisting Stand-off
Classification: Ams 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response Fastener   Material Document And Astm A313 Assn Std Single Material Response Spring   Classification: Astm A313 Assn Std Single Material Response Spring		
Classification: Astm A313 Assn Std Single Material Response Spring		Ams 5731 Assn Std Single Material Response Fastener Or Ams 5732 Assn Std Single Material Response Fastener
Thread Series Designator: Unjf		Astm A313 Assn Std Single Material Response Spring
	Thread Series Designator:	Unjf

## How to Order

Order this screws from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/CA22043-10-0360</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.