

Description

Fastener Length: 1-", Thread: 1/4-28

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | CA229042016 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5305-01-490-5349 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N CA2290-4-20-16 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 1.000 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Width Between Flats: | 0.357 Inches Minimum And 0.375 Inches Maximum |
| Internal Drive Style: | Hexagon |
| End Item Identification: | F/a-22 Raptor |
| Material Accommodated Thickness: | 0.625 Inches Nominal |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Part Name Assigned By Controlling Agency: | Screw, Captive, Hex Head |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/CA2290-4-20-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.