

**Description**

Fastener Length: 1-", Thread: 1/4-28

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	CA229042016
Minimum Qty (MOQ):	1
NSN:	5305-01-490-5349
Schedule B:	7318.15.6080
ECCN:	EAR99



## P/N CA2290-4-20-16 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.000 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Width Between Flats:</b>	0.357 Inches Minimum And 0.375 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>End Item Identification:</b>	F/a-22 Raptor
<b>Material Accommodated Thickness:</b>	0.625 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Screw, Captive, Hex Head
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/CA2290-4-20-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.