

Description

Fastener Length: 1-", Thread: 1/4-28

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CA229042016
Minimum Qty (MOQ):	1
NSN:	5305-01-490-5349
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N CA2290-4-20-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.000 Inches Nominal
Head Style:	Hexagon
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Width Between Flats:	0.357 Inches Minimum And 0.375 Inches Maximum
Internal Drive Style:	Hexagon
End Item Identification:	F/a-22 Raptor
Material Accommodated Thickness:	0.625 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw, Captive, Hex Head
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/CA2290-4-20-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.