



Military-Fasteners.com

P/N CA29041-3-2-9P

Description

Fastener Length: 1/2", Thread: 10-32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CA29041329P
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-520-3648
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N CA29041-3-2-9P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.562 Inches Nominal
Head Style:	Fillister
Internal Drive Style:	Cross Recess Type Ii
Material Accommodated Thickness:	0.245 Inches Minimum And 0.255 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Material:	Iron Alloy 660 Fastener
Material:	Steel Comp 302 Stand-off Or Steel Comp 303 Stand-off Or Steel Comp 304 Stand-off Or Steel Comp 305 Stand-off Or Steel Comp 316 Stand-off
Material:	Steel Comp 302 Primary Washer Or Steel Comp 303 Primary Washer Or Steel Comp 304 Primary Washer Or Steel Comp 305 Primary Washer Or Steel Comp 316 Primary Washer
Material:	Steel Comp 302 Secondary Washer
Material:	Steel Comp 302 Spring
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/CA29041-3-2-9P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.