

Description

thread: 10-32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CA3105103212
Minimum Qty (MOQ):	25
NSN:	5305-00-807-9026
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N CA3105-1032-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.511 Inches Minimum And 0.542 Inches Maximum
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.390 Inches Nominal
Washer Quantity:	1
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	28.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Primary Washer Outside Diameter:	0.620 Inches Minimum And 0.640 Inches Maximum
Primary Washer Style:	Flat External Teeth
Primary Washer Material Thickness:	0.015 Inches Minimum And 0.021 Inches Maximum
Material:	Steel Comp 1022 Overall
Thread Series Designator:	Unf

How to Order

Order this assembled washer screw from our inventory online by visiting <https://military-fasteners.com/screws/assembled+washer+screws/CA3105-1032-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.