

Description

thread: 10-32,

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CA310510328
Minimum Qty (MOQ):	25
NSN:	5305-00-807-9227
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N CA3105-1032-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.340 Inches Minimum And 0.380 Inches Maximum
Washer Quantity:	1
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	28.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Countersink Angle:	100.0 Degrees Nominal
Primary Washer Outside Diameter:	0.645 Inches Minimum And 0.665 Inches Maximum
Primary Washer Style:	Dome Internal Teeth
Primary Washer Material Thickness:	0.017 Inches Nominal
Secondary Washer Material Thickness:	0.017 Inches Nominal
Material:	Steel Comp 1022 Overall Or Steel Comp 1050 Overall
Thread Series Designator:	Unf

How to Order

Order this assembled washer screw from our inventory online by visiting <https://military-fasteners.com/screws/assembled+washer+screws/CA3105-1032-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.