

P/N CA3105-1032-9

Description

thread: 10-32

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: CA310510329

Minimum Qty (MOQ): 25

NSN: 5305-00-966-6583

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N CA3105-1032-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.344 Inches Minimum And 0.437 Inches Maximum
Fastener Length:	0.531 Inches Minimum And 0.562 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.340 Inches Minimum And 0.380 Inches Maximum
Washer Quantity:	1
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	28.0 Rockwell C Minimum Overall And 34.0 Rockwell C Maximum Overall
Countersink Angle:	100.0 Degrees Nominal
Primary Washer Outside Diameter:	0.645 Inches Minimum And 0.665 Inches Maximum
Primary Washer Style:	Split
Primary Washer Material Thickness:	0.017 Inches Nominal
Material:	Steel Comp 1022 Overall
Thread Series Designator:	Unf

How to Order

Order this assembled washer screw from our inventory online by visiting https://military-fasteners.com/screws/assembled+washer+screws/CA3105-1032-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.