

Description

CCR244SS-3-04 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CCR244SS3-04](#)

SKU / Model:	CCR244SS304
Minimum Qty (MOQ):	100
NSN:	5320-01-215-9833
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CCR244SS-3-04 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.148 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Heat Treatment:	Annealed Sleeve
Material:	Steel Comp 1008 Stem
Material:	Steel Comp 1018 Sleeve
Surface Treatment:	Cadmium And Chromate Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR244SS-3-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.