

Description

diameter: 3/32", grip range: 0.063-0.125", CCR244 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CCR244SS-03-02](#) [CCR244SS3-2](#) [CCR244SS-3-02](#)

SKU / Model:	CCR244SS302
Minimum Qty (MOQ):	100
NSN:	5320-00-204-5440
Schedule B:	8803.30.0010
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CCR244SS3-02 Specifications

Fastener Length:	0.281 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.0928 Inches Minimum And 0.0968 Inches Maximum
Head Major Diameter:	0.140 Inches Minimum And 0.148 Inches Maximum
Expansion Device:	Plain Stem-type T
Grip Length:	0.063 Inches Minimum And 0.125 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 1012 Sleeve
Material:	Steel Comp 1012 Stem
Material Document And Classification:	66 Fed Std All Material Responses Stem
Material Document And Classification:	66 Fed Std All Material Responses Sleeve
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Cadmium Stem And Chromate Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR244SS3-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.