

**Description**

diameter: 3/32", grip range: 0.063-0.125", CCR244 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CCR244SS-03-02](#) [CCR244SS3-2](#) [CCR244SS-3-02](#)

SKU / Model:	CCR244SS302
Minimum Qty (MOQ):	100
NSN:	5320-00-204-5440
Schedule B:	8803.30.0010
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CCR244SS3-02 Specifications

<b>Fastener Length:</b>	0.281 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.0928 Inches Minimum And 0.0968 Inches Maximum
<b>Head Major Diameter:</b>	0.140 Inches Minimum And 0.148 Inches Maximum
<b>Expansion Device:</b>	Plain Stem-type T
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Comp 1012 Sleeve
<b>Material:</b>	Steel Comp 1012 Stem
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Stem
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Sleeve
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment:</b>	Cadmium Stem And Chromate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR244SS3-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.