

Description

flush head, steel, diameter: 3/32", grip range: 0.251" - 0.312

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CCR244SS-3-05

SKU / Model:	CCR244SS305
Minimum Qty (MOQ):	100
NSN:	5320-01-618-9656
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CCR244SS3-05 Specifications

Head Style:	Flat Countersunk Undercut
Head Height:	0.21 Inches Nominal
Shank Diameter:	0.097 Inches Minimum And 0.101 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.148 Inches Nominal
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Heat Treatment:	Annealed Sleeve
Material:	Steel Comp 1018 Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR244SS3-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.