

Description

flush head, steel, diameter: 3/32", grip range: 0.251" - 0.312

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[CCR244SS-3-05](#) [CCR244SS3-5](#)

| | |
|-------------------------|---|
| SKU / Model: | CCR244SS305 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-618-9656 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N CCR244SS3-05 Specifications

| | |
|-----------------------------|--|
| Head Style: | Flat Countersunk Undercut |
| Head Height: | 0.21 Inches Nominal |
| Shank Diameter: | 0.097 Inches Minimum And 0.101 Inches Maximum |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.148 Inches Nominal |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Heat Treatment: | Annealed Sleeve |
| Material: | Steel Comp 1018 Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR244SS3-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.