

**Description**

flush head, steel, diameter: 3/32", grip range: 0.251" - 0.312

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CCR244SS-3-05](#) [CCR244SS3-5](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | CCR244SS305                                 |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-01-618-9656                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

## P/N CCR244SS3-05 Specifications

|                             |  |
|-----------------------------|--|
| <b>Head Style:</b>          | Flat Countersunk Undercut                      |
| <b>Head Height:</b>         | 0.21 Inches Nominal                            |
| <b>Shank Diameter:</b>      | 0.097 Inches Minimum And 0.101 Inches Maximum  |
| <b>Shank Style:</b>         | Self-plugging High Clinch Shank                |
| <b>Head Major Diameter:</b> | 0.148 Inches Nominal                           |
| <b>Countersink Angle:</b>   | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| <b>Heat Treatment:</b>      | Annealed Sleeve                                |
| <b>Material:</b>            | Steel Comp 1018 Overall                        |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR244SS3-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.