

## P/N CCR244SS3-5

## **Description**

Nutplate rivet, CCR244 series

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

CCR244SS3-05

SKU / Model: CCR244SS35

Minimum Qty (MOQ): 100

NSN: 5320-01-463-8466

Schedule B: 7318.23.0000

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# **P/N CCR244SS3-5 Specifications**

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	2.3 Millimeters Minimum And 2.4 Millimeters Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	3.7 Millimeters Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	7.9 Millimeters Minimum And 9.5 Millimeters Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 1008 Stem
Material:	Steel Comp 1018 Body

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/CCR244SS3-5">https://military-fasteners.com/rivets/blind+rivets/CCR244SS3-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.