

P/N CCR244SS3-7

Description

CCR244SS3-7 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

CCR244SS3-07

SKU / Model: CCR244SS37

Minimum Qty (MOQ): 100

NSN: 5320-01-282-1572

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









^{*} See page 2 for technical characteristics

P/N CCR244SS3-7 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
neau Style.	Trush (hat) Countersunk (included Aligie - Less Than 155 Deg W Of W/o Chamler)
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.140 Inches Minimum And 0.148 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.376 Nominal Mils And 0.437 Nominal Centimeters
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Stem Finish Is Rust Prev. (oil Base)
Material:	Steel Comp 1018 Overall
Surface Treatment:	Cadmium Body And Chromate Body
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Body

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CCR244SS3-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.