

Description

CCR244SS3-7 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CCR244SS3-07](#)

SKU / Model:	CCR244SS37
Minimum Qty (MOQ):	100
NSN:	5320-01-282-1572
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CCR244SS3-7 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.140 Inches Minimum And 0.148 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.376 Nominal Mils And 0.437 Nominal Centimeters
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Stem Finish Is Rust Prev. (oil Base)
Material:	Steel Comp 1018 Overall
Surface Treatment:	Cadmium Body And Chromate Body
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Body

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR244SS3-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.