

**Description**

flat head, dry film

\* Manufacturer certifications are shipped with your order FREE of charge

[Order this part online](#)**Additional Information****Alternate Part Numbers**MS20605R4W5 CCR264CS4-05 CCR264CS-4-5

SKU / Model:	CCR264CS405
Minimum Qty (MOQ):	100
NSN:	5320-01-232-9841
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N CCR264CS-4-05 Specifications

<b>Fastener Length:</b>	0.506 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.123 Inches Minimum And 0.128 Inches Maximum
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.225 Inches Maximum
<b>Expansion Device:</b>	Threaded Stem
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.251 Inches Minimum And 0.312 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Steel Comp 305 Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Astm A493 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264CS-4-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.