

Description

diameter: 3/32", grip range: 0.313" - 0.375", flush head, pull thru, corrosion resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CCR264CS-3-06](#) [CCR264CS3-6](#)

SKU / Model:	CCR264CS306
Minimum Qty (MOQ):	100
NSN:	5320-01-051-1634
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CCR264CS3-06 Specifications

Fastener Length:	0.530 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Head Height:	0.040 Inches Nominal
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
Expansion Device:	Threaded Stem
Lubrication:	Dry Film
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Shear Strength:	185 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 305 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astm-a-493 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq=p=35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264CS3-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.