

Description

diameter: 3/32", grip range: 0.313" - 0.375", flush head, pull thru, corrosion resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CCR264CS-3-06](#) [CCR264CS3-6](#)

| | |
|-------------------------|---|
| SKU / Model: | CCR264CS306 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-051-1634 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N CCR264CS3-06 Specifications

| | |
|---|--|
| Fastener Length: | 0.530 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Head Height: | 0.040 Inches Nominal |
| Shank Diameter: | 0.092 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.175 Inches Minimum And 0.183 Inches Maximum |
| Expansion Device: | Threaded Stem |
| Lubrication: | Dry Film |
| Grip Length: | 0.313 Inches Minimum And 0.375 Inches Maximum |
| Shear Strength: | 185 Single Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Steel Comp 305 Stem |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve |
| Material Document And Classification: | Astm-a-493 Assn Std Single Material Response Stem |
| Surface Treatment: | Passivate Stem |
| Surface Treatment Document And Classification: | Qq=p=35 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264CS3-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.