

P/N CCR264CS3-07

Description

diameter: 3/32", grip range: 0.376" - 0.437", flush head, corrosion resistant

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS20605R3W7 CCR264CS3-7

SKU / Model: CCR264CS307

Minimum Qty (MOQ):

NSN: 5320-01-585-3260

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N CCR264CS3-07 Specifications

Fastener Length:	0.592 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Lubrication:	Solid Film
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 305 Stem
Surface Treatment:	Passivate Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CCR264CS3-07 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CCR264CS3-07 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/CCR264CS3-07 and selecting the quantity you want then click "add to cart".