

**Description**

diameter: 3/32", grip range: 0.376" - 0.437", flush head, corrosion resistant

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS20605R3W7](#) [CCR264CS3-7](#)

SKU / Model:	CCR264CS307
Minimum Qty (MOQ):	100
NSN:	5320-01-585-3260
ECCN:	EAR99



## P/N CCR264CS3-07 Specifications

<b>Fastener Length:</b>	0.592 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.092 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Lubrication:</b>	Solid Film
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Steel Comp 305 Stem
<b>Surface Treatment:</b>	Passivate Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264CS3-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.