

Description

Pull-thru rivet, CCR246 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	CCR264CS34IPR
Minimum Qty (MOQ):	100
NSN:	5320-01-420-6113
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CCR264CS3-4IPR Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.183 Inches Nominal
Expansion Device:	Threaded Sleeve
Grip Length:	0.405 Inches Maximum
Countersink Angle:	101.0 Degrees Nominal
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 305 Stem
Material Document And Classification:	Ams5731 Assn Std Single Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264CS3-4IPR> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.