

Description

Pull-thru rivet, CCR246 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | CCR264CS34IPR |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-420-6113 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N CCR264CS3-4IPR Specifications

| | |
|--|--|
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.092 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.183 Inches Nominal |
| Expansion Device: | Threaded Sleeve |
| Grip Length: | 0.405 Inches Maximum |
| Countersink Angle: | 101.0 Degrees Nominal |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Steel Comp 305 Stem |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264CS3-4IPR> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.