

**Description**

Fastener Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CCR264CS3-06](#)

SKU / Model:	CCR264CS36
Minimum Qty (MOQ):	100
NSN:	5320-01-051-1634
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N CCR264CS3-6 Specifications

<b>Fastener Length:</b>	0.530 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Head Height:</b>	0.040 Inches Nominal
<b>Shank Diameter:</b>	0.092 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.175 Inches Minimum And 0.183 Inches Maximum
<b>Expansion Device:</b>	Threaded Stem
<b>Lubrication:</b>	Dry Film
<b>Grip Length:</b>	0.313 Inches Minimum And 0.375 Inches Maximum
<b>Shear Strength:</b>	185 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Steel Comp 305 Stem
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
<b>Material Document And Classification:</b>	Astm-a-493 Assn Std Single Material Response Stem
<b>Surface Treatment:</b>	Passivate Stem
<b>Surface Treatment Document And Classification:</b>	Qq=p=35 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264CS3-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.