

Description

CCR264CS4-03 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[CCR264CS-4-3](#) [MS20605R4W3](#) [CCR264CS4-3](#) [CCR264CS-4-03](#)

| | |
|-------------------------|---|
| SKU / Model: | CCR264CS403 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-248-2217 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CCR264CS4-03 Specifications

| | |
|---|--|
| Fastener Length: | 0.381 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.123 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.225 Inches Maximum |
| Expansion Device: | Threaded Stem |
| Lubrication: | Dry Film |
| Grip Length: | 0.126 Inches Minimum And 0.187 Inches Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Sleeve |
| Material: | Steel Comp 305 Stem |
| Material Document And Classification: | Ams5731 Assn Std Single Material Response Sleeve |
| Material Document And Classification: | Astm-a-493 Assn Std Single Material Response Stem |
| Surface Treatment: | Passivate Stem |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Stem |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264CS4-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.