

Description

Flush head, corrosion resistant, diameter: 1/8", grip range: 0.188" - 0.250

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CCR264CS4-4](#)

SKU / Model:	CCR264CS404
Minimum Qty (MOQ):	100
NSN:	5320-01-356-6176
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N CCR264CS4-04 Specifications

Fastener Length:	0.443 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.1230 Inches Minimum And 0.1280 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.2210 Inches Minimum And 0.2290 Inches Maximum
Expansion Device:	Threaded Stem
Lubrication:	Dry Film
End Item Identification:	W/s:aircraft, B-2 Bomber (atb); Aircraft, B-1b
Grip Length:	0.1880 Inches Minimum And 0.2500 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 305 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astm-a-493 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264CS4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.