

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	CCR264CS43
Minimum Qty (MOQ):	100
NSN:	5320-01-248-2217
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in a sans-serif font.

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N CCR264CS4-3 Specifications

Fastener Length:	0.381 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.123 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.225 Inches Maximum
Expansion Device:	Threaded Stem
Lubrication:	Dry Film
Grip Length:	0.126 Inches Minimum And 0.187 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 305 Stem
Material Document And Classification:	Ams5731 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astm-a-493 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264CS4-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.