

P/N CCR264CS4-9

Description

Fastener Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Minimum Qty (MOQ): 100 NSN: 5320-01-330-5332	SKU / Model:	CCR264CS49
NSN: 5320-01-330-5332	Minimum Qty (MOQ):	100
NSN. 3320-01-330-3332	NSN:	5320-01-330-5332
Schedule B: 7318.23.0000	Schedule B:	7318.23.0000

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed



^{*} See page 2 for technical characteristics

P/N CCR264CS4-9 Specifications

Fastener Length:	0.774 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.123 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.221 Inches Minimum And 0.229 Inches Maximum
Expansion Device:	Threaded Stem
Lubrication:	Dry Film
End Item Identification:	W/s: Aircraft, B-1b; Support Equipment (se), B-2 Bomber; Aircraft, B-2 Bomber (atb)
Grip Length:	0.500 Inches Minimum And 0.562 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 305 Stem
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astm A493 Assn Std Single Material Response Stem
Surface Treatment:	Passivate Stem
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/CCR264CS4-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.