

Description

diameter: 3/32", grip range: 0.438" - 0.50", flush head, steel, CCR264 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

CCR264SS3-8

SKU / Model:	CCR264SS308
Minimum Qty (MOQ):	100
NSN:	5320-01-622-6568
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CCR264SS3-08 Specifications

Fastener Length:	0.578 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
End Item Identification:	A-10 Wrp
Grip Length:	0.438 Inches Minimum And 0.500 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 1018 Sleeve
Material:	Steel Stem
Surface Treatment:	Cadmium And Chromate Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264SS3-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.