

P/N CCR264SS3-4

Military-Fasteners.com

Description

Fastener Length: 3/8", Cherry pull thru rivet, CCR264 series rivet

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

Alternate Part Numbers

CCR264SS3-04	
SKU / Model:	CCR264SS34
Minimum Qty (MOQ):	100
NSN:	5320-01-322-7026
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N CCR264SS3-4 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Pull Through Hollow Shank
Head Major Diameter:	0.183 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 1008 Stem
Material:	Steel Comp 1018 Body
Surface Treatment:	Cadmium Body And Chromate Body
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Fed Spec Single Treatment Response Body

How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/CCR264SS3-4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.