

Description

diameter: 1/8", grip range: 0.188" - 0.25", flush head, steel, CCR264 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CCR264SS4-4](#)

| | |
|--------------------|------------------|
| SKU / Model: | CCR264SS404 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-313-7618 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N CCR264SS4-04 Specifications

| | |
|---|--|
| Fastener Length: | 0.337 Inches Minimum And 0.357 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.092 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.183 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Comp 1008 Stem |
| Material: | Steel Comp 1018 Mechanical Lock |
| Surface Treatment: | Cadmium Bolt |
| Surface Treatment Document And Classification: | Qq-p-416,ty li Fed Spec Single Treatment Response Bolt |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264SS4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.