

Description

diameter: 1/8", grip range: 0.188" - 0.25", flush head, steel, CCR264 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CCR264SS4-4](#)

SKU / Model:	CCR264SS404
Minimum Qty (MOQ):	100
NSN:	5320-01-313-7618
ECCN:	EAR99



* See page 2 for technical characteristics

P/N CCR264SS4-04 Specifications

Fastener Length:	0.337 Inches Minimum And 0.357 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.092 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.183 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 1008 Stem
Material:	Steel Comp 1018 Mechanical Lock
Surface Treatment:	Cadmium Bolt
Surface Treatment Document And Classification:	Qq-p-416,ty li Fed Spec Single Treatment Response Bolt

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264SS4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.