

## Description

diameter: 1/8", grip range: 0.188" - 0.25", flush head, steel, CCR264 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[CCR264SS4-4](#)

SKU / Model:	CCR264SS404
Minimum Qty (MOQ):	100
NSN:	5320-01-313-7618
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N CCR264SS4-04 Specifications

<b>Fastener Length:</b>	0.337 Inches Minimum And 0.357 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.092 Inches Minimum And 0.097 Inches Maximum
<b>Shank Style:</b>	Self-plugging High Clinch Shank
<b>Head Major Diameter:</b>	0.183 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.188 Inches Minimum And 0.250 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Comp 1008 Stem
<b>Material:</b>	Steel Comp 1018 Mechanical Lock
<b>Surface Treatment:</b>	Cadmium Bolt
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty li Fed Spec Single Treatment Response Bolt

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR264SS4-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.