

P/N CCR264SS4-4

Military-Fasteners.com

Description

Fastener Length: 3/8", CCR264 series rivet

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | CCR264SS44 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-01-313-7618 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |



P/N CCR264SS4-4 Specifications

| Fastener Length: | 0.337 Inches Minimum And 0.357 Inches Maximum |
|--|--|
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.092 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Self-plugging High Clinch Shank |
| Head Major Diameter: | 0.183 Inches Nominal |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.188 Inches Minimum And 0.250 Inches Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Comp 1008 Stem |
| Material: | Steel Comp 1018 Mechanical Lock |
| Surface Treatment: | Cadmium Bolt |
| Surface Treatment Document And Classification: | Qq-p-416,ty li Fed Spec Single Treatment Response Bolt |

How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/CCR264SS4-4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.