

**Description**

diameter: 3/32", grip range: 0.046" - 0.062", universal head, corrosion resistant

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[CCR274CS3-1](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | CCR274CS301                                 |
| Minimum Qty (MOQ):      | 100   |
| NSN:                    | 5320-01-337-4943                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N CCR274CS3-01 Specifications

|   |   |
|---|---|
| <b>Head Style:</b>                                    | Undercut Pan No. 2                                |
| <b>Head Height:</b>                                   | 0.040 Inches Minimum And 0.050 Inches Maximum     |
| <b>Shank Diameter:</b>                                | 0.092 Inches Minimum And 0.097 Inches Maximum     |
| <b>Shank Style:</b>                                   | Self-plugging High Clinch Shank                   |
| <b>Head Major Diameter:</b>                           | 0.178 Inches Minimum And 0.196 Inches Maximum     |
| <b>Expansion Device:</b>                              | Serrated Stem-type W                              |
| <b>Lubrication:</b>                                   | Solid Film  |
| <b>Grip Length:</b>                                   | 0.062 Inches Maximum                              |
| <b>Material:</b>                                      | Iron Alloy 660 Sleeve                             |
| <b>Material:</b>                                      | Steel Comp 305 Stem                               |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Sleeve |
| <b>Material Document And Classification:</b>          | Astm A493 Assn Std Single Material Response Stem  |
| <b>Surface Treatment:</b>                             | Passivate Stem                                    |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Stem   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR274CS3-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.