

Description

diameter: 3/32", grip range: 0.251" - 0.312", universal head, corrosion resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[CCR274CS3-5](#) [CCR274CS-3-5](#)

SKU / Model:	CCR274CS305
Minimum Qty (MOQ):	100
NSN:	5320-01-180-5134
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N CCR274CS3-05 Specifications

Fastener Length:	0.390 Inches Nominal
Head Style:	Universal
Head Height:	0.040 Inches Nominal
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Self-plugging High Clinch Shank
Head Major Diameter:	0.187 Inches Nominal
Expansion Device:	Threaded Stem
Grip Length:	0.390 Inches Nominal
Material:	Iron Alloy 660 Sleeve
Material:	Steel Comp 305 Stem
Material Document And Classification:	Ams5736 Assn Std Single Material Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/CCR274CS3-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.